Bibliography

- 1. U.K. Specification MPT 1550 Issue 1, September 1993.
- U.K. Radiocommunications Agency: Report of the 40 GHz MVDS Working Group, November 1993.
- 3. CEPT Recommendation for MVDS harmonised band, T/R 52-01E.
- 4. CCIR Report 338-6 Propagation Data and Prediction Methods for Terrestrial Line of Sight.
- 5. CCIR Report 338-6 Propagation Data and Prediction Methods for Terrestrial Line of Sight.
- 6. CCIR Report 719-3 Attenuation by Atmospheric Gases.
- Scott, U.K. Radiocommunications Agency Working Group Paper, 40 GWG (91)39.
 Atmospheric constants.
- 8. CCIR Report 721-3 Attenuation by Hydrometeors.
- 9. Harden, Norbury, White; Microwave, Optics and Acoustics, July 1978; Attenuation by rain in the UK.
- 10. CCIR Report 563-4; Radiometeorological Data.
- 11. CCIR Report 814: Depolarization effects of rain.
- 12. CCIR Report 715-2; Propagation by Diffraction.
- 13. CCIR Report 405-5; Subjective Assessment of TV quality.
- 14. CCIR Recommendation 654; Subjective quality of TV pictures
- 15. CCIR Report 959-1; Experimental results relating TV quality to objective impairment.
- Oliphant, Taylor and Misson; Electronics and Communication Engineering Journal, May/June 1989; Visibility of noise in System PAL-I colour TV.
- 17. CCIR Report 637-3; Signal to Noise Ratio in TV.
- 18. Haverson, Dutronc, Dobbie and Court; International Journal of Satellite Communications, Volume 9 (1991); Required Protection Ratios for Cofrequency PAL.
- 19. A.V. Harris (UK-RA): The UK Technical and Regulatory Framework Established for Analogue MVDS at 40 GHz, IBC, Amsterdam, 1994.

Microwave

Video


Distribution

Systems



PHILIPS


Service Delivery Chain



Philips Microwave



MVDS TRANSMISSION SYSTEM



Philips Microwave



MVDS Position

- * Cable-like features Broad band
 - Interactive possibility
- * DTH-like features Speed
 - Low marginal cost

Where?

- * Remote population pocket; Infill
- * Sparsely populated areas
- * Areas requiring rapid installation or upgrade

Philips Microwave



Why Today's Interest?

- * Market Fragmentation
- * Deregulation / Competition
- * Converging Markets
 - entertainment
 - telecommunications
 - financial services
- * Maturing Technology





Regulatory Position

- * World ITU/WARC Broadcasting bands 12, 29, 42 GHz
- * USA MVDS Pioneer's Licence 29 GHz
- * Europe CEPT MVDS band 42 GHz
- * UK 1990 Broadcasting Act LDO Licence Wireless Telegraphy Licence MPT 1550





IBC 94

The UK technical and regulatory framework established for multipoint video distribution systems at 40 GHz

A V Harris Radiocommunications Agency, UK 20 September 1994



System Design Aspects

- Frequency modulation, 26 MHz channel bandwidth
- Commonality with Fixed Satellite Service / Direct To Home parameters
- 29.5 MHz co-polar channel spacing
- 14.75 MHz cross-polar channel interleaving
- 4 channel groups of 32 channels, horizontal and vertical polarisations
- PAL/I and other transmission standards, digital transmission not precluded



Quality Criteria

• Carrier to noise ratio (C/N) of 12 dB

• CCIR Grade 4 "satisfactory" picture grade

• Service availability: all but 1% Worst Month (0.3% t) (same availability as specified for the Broadcasting Satellite Service)



Performance specification and licensing regime

- Performance specification issued by the RA as MPT1550 to be used for type approval purposes, controlling spectrum utilisation parameters
- MVDS services licensed and franchises awarded under the Local Delivery Services (LDS) provisions of the UK Broadcasting Act 1990
- Technical plans for MVDS will be assessed by the ITC and RA for coverage and interference potential
- Terrain shielding and antenna directivity to be used to minimise interference to other existing or potential MVDS operators
- 64 ° sector coverage antenna should ensure minimum coverage area of 13 km²



Propagation Aspects At 40 GHz

- Atmospheric absorption due to oxygen and water vapour is 0.15 dB/km
- 1% WM (0.3% time) availability gives 7 mm/hour rainfall rate equivalent to 2.2 dB/km for UK, CCIR rain zone G
- Rain induced cross-polar discrimination is 25 dB over 5 km path at 25 mm/h
- Frequency re-use distance under investigation; propagation experiments under way in UK at Rutherford Appleton Laboratory and Essex University

MVDS Architecture

* Per Franchise - Programme capture

- Subscriber management

- Encryption

* Per Cell

- Signal transport

- Signal broadcast

- Return path & switch

* Per Household - RX downconverter


- TX upconverter

* Per Consumer - TX/RX indoor unit

Smartcard authorisation

Philips Microwave





Transmitter Cost Estimate

- * Based on RA Report
- * 25 + 5 channels £27,500 ... 47,500
- * 32 + 4 channels £33,000 ... 57,000
- * Excludes
- programme generation/capture
- subscriber management
- encryption
- planning/installation





Receiver Cost Comparison

DBS

MVDS

Cable

-

-

Antenna

50 cm dish

20 cm dish

Conversion #1

FET DRO

Varactor Mixer pair

Conversion #2

LNA

LNA

MMIC

MMIC

FET DRO

FET DRO

950...2050 MHz

MMIC

MMIC

Outdoor Unit

£30 ... 60

£65 ... 130

Indoor Unit

£115

£115

Installation

£40

£40

- * Cost determine by volume
- * Cost of 42 GHz devices not prime





Cost Comparison with Cable (1)

- * Based on RA report
- * Underground cable
- * 50000 households

Penetration

	25%	33%	50%
Per subscriber	£1300	£1000	£700
Assign TV	£ 780	£ 600	£ 420
Assign telephony	£ 520	£ 400	£ 280

Philips Microwave



Breakeven Community (cf. cable)

Penetration

25% 33% 50%

Total cost £780 £600 £420

Typical RX (£265) (£265) (£265)

Shared TX £515 £335 £155

Typical TX (£ 55k) (£ 55k) (£ 55k)

Community 427 425 710

Philips Microwave



Revenue

(Courtesy of FSN Ltd, Cambridge)

- * Franchise 100 000 households
- * Television 80% coverage
 - 20% penetration
 - **16000** customers
 - £18 revenue/customer p.m.
 - £3,46M revenue p.a.
 - (£1,12M) programming costs

Net revenue p.a. - £2,34M

- * Telephony 25% residential penetration
 - **20000** customers
 - £13 revenue/customer p.m.
 - 15% business penetration
 - 800 business lines
 - £200 revenue/customer p.m.

Net revenue p.a. - £5,04M

Philips Microwave



Digital Requirement

* MPEG-2 with DVB shell

CDI quality 1,6 MBit/s
Typical content 3-5 MBit/s
Rapid movement >8 MBit/s

- * Cable service 64 QAM
- * Satellite service QPSK

prETS 300xxx/6 May 1994 FEC for 10 EXP-11 at 8dB C/N

Redundancy 15 ... 100% Useful bit rate 19...34 MBit/s

* Thus, MVDS

Programmes/transponder 4 ... 12 System gain improvement ~4 dB

Philips Microwave



Digital Migration

- * QPSK or OQPSK
- * Standard Master Head End
- * Review TX
- * Transparent RXO
- * Standard RXI





The Way Forward

- * Technology Propagation
 - Protection ratio
 - Digital modulation
- * Regulatory Digital
 - Duplex
 - Extend to ETS
- * Commercial Eurobell West Kent
 - Next LDO round

Philips Microwave



Duplex (interactive) MVDS

* Copper twisted pair


* Mobile telephony - GSM - DECT

* In-band radio - modulation

- frequency plan









EUROBELL